

MIKSAN 112 4A EX SERIES EX-PROOF



3-Phase 400V 50Hz

Duty Type : S1
Degree of protection : IP65
Insulation Class : F (155°C)
Mounting : B14

ELECTRICAL DESIGN

Rated power(W) : 4000
Speed(rpm) : 1445
Rated current(A) : 8,50
Torque –Mn(Nm) : 26,50
Cos ϕ : 0,81
Efficiency (%) : 86,6

LOCKED ROTOR TORQUE

Locked rotor Current– Ia(A) : 59,50
Ia / In : 7,0
Locked rotor Torque- Ma(Nm) : 55,65
Ma / Mn : 2,1

MECHANICAL DESIGN

Frame : Aluminum
End Shields : Aluminum
Terminal Box : Aluminum
Cable gland : M20x1,5 EX

BEARING ARRANGEMENT

Drive End


6206 ZZ C3

Non Drive End



6206 ZZ C3

Paint : None

Weight : 29,8 kg



B3-B6-B7-B8-V5-V6



L	P	N	M	T	øAC	LA	S	AD	TB/TL	E	øD	øDB	GA	FxGD
387	160	110	130	3.5	218	16.0	M8	190	122	60	28	M10	31	8x8

IEP 16 ATEX 0433X

II 2G Ex db IIC T4 Gb

II 2D Ex tb IIIC T120°C Db,IP65