

MIKSAN 56 4A EX SERIES EX-PROOF




3-Phase 230Δ/400Y V 50Hz

Duty Type : S1
Degree of protection : IP66
Insulation Class : F (155°C)
Mounting : B3

ELECTRICAL DESIGN

Rated power(W) : 90
Speed(rpm) : 1350
Rated current(A) : 0,41
Torque –Mn(Nm) : 0,65
Cos φ : 0,65
Efficiency (%) :



LOCKED ROTOR TORQUE

Locked rotor Current– Ia(A) : 1,1
Ia / In : 2,7
Locked rotor Torque- Ma(Nm) : 1,56
Ma / Mn : 2,4

MECHANICAL DESIGN

Frame : Aluminum
End Shields : Aluminum
Terminal Box : Aluminum
Cable gland : M20x1,5 EX

BEARING ARRANGEMENT

Drive End


6201 ZZ C3

Non Drive End



6201 ZZ C3

Paint : None

Weight : 4,0 kg



B3-B6-B7-B8-V5-V6



L	H	HD~	A	AB	øAC	B	BB	K	K1	C	E	øD	øDB	GA	FxGD
182	56	188	90	110	108	71	81	6	7	36	20	9	-	10	3x3

IEP 16 ATEX 0433X

II 2G Ex db IIC T4 Gb

II 2D Ex tb IIIC T120°C Db,IP66