

MIKSAN 100 4A IE3 EX SERIES EX-PROOF




3-Phase 400V 50Hz

Duty Type : S1
Degree of protection : IP66
Insulation Class : F (155°C)
Mounting : B3

ELECTRICAL DESIGN

Rated power(W) : 2200
Speed(rpm) : 1430
Rated current(A) : 4,90
Torque –Mn(Nm) : 14,60
Cos ϕ : 0,76
Efficiency (%) : 86,7



LOCKED ROTOR TORQUE

Locked rotor Current– Ia(A) : 27,44
Ia / In : 5,6
Locked rotor Torque- Ma(Nm) : 36,66
Ma / Mn : 2,1

MECHANICAL DESIGN

Frame : Aluminum
End Shields : Aluminum
Terminal Box : Aluminum
Cable gland : M20x1,5 EX

BEARING ARRANGEMENT

Drive End


6206 ZZ C3

Paint : None



Non Drive End

Weight : 23,4 kg

6206 ZZ C3



B3-B6-B7-B8-V5-V6



L	H	HD~	A	AB	øAC	B	BB	K	K1	C	E	øD	øDB	GA	FxGD
375	100	274	160	192	194	140	165	12	18	63	60	28	M10	31	8x8

IEP 16 ATEX 0433X

II 2G Ex db IIC T4 Gb

II 2D Ex tb IIIC T120°C Db,IP66